D series

## ALLU DH 3-23





## Efficient material processing

The ALLU DH 3-23 is a purpose built screening bucket that makes the perfect attachment for construction, quarrying and recycling applications.

Capable of processing any material that can be screened and sorted, the DH 3-23 transforms materials into valuable products making processing jobs more efficient, more environmentally friendly, and minimising the need for transportation of waste or replacement materials.

## Transforms waste -wet or dry

It produces homogenous end-product even with wet materials due to patented design of TS technology that ensure the bucket is cloq-free.

ALLU DH 3-23 comes with a ALLU Sensor that gathers data on location, runtime, operating angle and more. Download the ALLU App\* to view and analyse the data.

operating hours

operator training

maintenance intervals

safety guide

product specifications

applications

manuals

\*blue tooth connectivity



# ALLU DH 3-23





## DH 3-23 key specs







weight

carrier weight

volume

2,960 kg

26-45 t (excavator)

1.65 - 2.16m<sup>3</sup>

14-30 t (wheel loader)

### ALLU DH 3-23 specifications

26 - 45 Excavator weight (t) 14 - 30 Wheel loader weight (t) Volume (m<sup>3</sup>) 1.65 - 2.16Screen area (m<sup>2</sup>) 1.7 Oil flow - X/XHD (lpm) 140 - 235 Oil flow - TS (Ipm) 190 - 315 Weight (kg) 2.960

Check carrier allowed attachment weight from carrier manufacturer. Check application requirements.

#### **DRUMS**

- TS
- X
- XHD

#### **BLADE SIZES\***

- TS08 (approx. 0 10mm fragment size)\*\*
- TS16 (approx. 0 20mm fragment size) \*\*
- TS25 (approx. 0 30mm fragment size) \*\*
- TS35 (approx. 0 45mm fragment size) \*\*
- X75 and X100 (aeration and stabilisation)
- XHD 25/40/60
- \* dual or triple fragment sizes with switch kit
- \*\* standard and axe

#### **ACCESSORIES**

- Extra sides
- Directional valve
- Switch kit • ALLU Sensor
- Drain line eliminator
- Drain line relief valve
- ALLU App

Specifications are subject to change without notice.

## Drum and Blade options

TS Screening drum

TS Shredding drum





various blade sizes

change of fragment size without dismantling drums

Stabilising, mixing, aerating & shredding drum (X 75/100)

Screening and crushing drum (XHD 25/40/60)





changeable blades



TS Standard blade for screening



TS Axe blade for shredding







for most applications and materials. Good durability.



Long blade 40 & 60 XHD

for screening and aerating compost and other soft materials to increase capacity.



#### X blade

For stabilising, mixing, aerating and crushing. Suitable for X75 and X100 drums.